



**GT-5504**

**Make:** ALmix

**Size:** 400 TPH

**Type:** Double Drum Plant

**Dryer:**

- ALMmx 90" OD x 38' long Stationary Counterflow Dryer
- Trunnion Driven with (4) 30 HP drives and railroad bearings
- Genco® UFII-100 Tri-Fuel Burner capable of burning oil, gas, and propane and is currently fired on Natural Gas
- Equipped with a Hydrocarbon Emissions Chamber
- Slinger Belt Feed Conveyor
- Early Entry RAP Collar
- Full Length Frame and Support Legs

**Rotary Mixer:**

- ALmix 6' dia. X 16' long Single Tire Stationary Rotary Mixer Assembly
- Trunnion Driven with (2) 30 HP Drives and railroad bearings
- Fully insulated and skinned
- Emissions Fan and Ductwork feed back to the burner

**Dust Collection:**

- ALmix Roto-Air Stationary Baghouse with 720 Envelope Style Bags
- Auger Style Dust Removal
- Twin City size 490 Exhaust Fan with a single 200 HP drive and newly reconditioned motor
- Gencor® Volumetric Dust Run-around System consisting of a dust pod feeding the Rotary Mixer
- All interconnecting duct work also included

**Virgin Aggregate System:**

- (7) ALmix 9' x 13' Aggregate Feed Bins with 5 HP Drive Packages
- ALmix nominal 95' Collector Conveyor with 15 HP Drive Package
- Intermediate Truss Conveyor feeding the screen deck
- 5' x 10' single deck scalping screen with 3 HP drive and support stand
- ALmix nominal 65' long virgin feed Scale Conveyor with wind guards and sample chute

**Recycle System:**

- Recycle System consists of a single 8' x 12' bin with an inclined feeder conveyor feeding a 30" wide x nominal 65' long Recycle Scale Conveyor which feeds the Rotary Mixer Assembly

**AC System:**

- Two (2) ALmix nominal 40,000 gallon vertical coiled only AC tank, one w/ Agitator one without.
- One (1) Power Controls, Inc. nominal 30,000 gallon vertical coiled only AC tank with agitator.
- ALmix model ALH-15, 1.5 M.B.T.U Hot Oil Heater with a New Webster burner
- One (1) 3" Unloading Pump with 15 HP Drive
- One (1) 3" Pump Metering Skid



GT-5504

**Silo System:**

- Two (2) Aesco 200 Ton Capacity Stationary Asphalt Storage Silos
- Hot Oil Cone Heat with Electric Gate Heat
- Square Batchers and Fully Welded Frame and Support Legs
- Astec® nominal 100' long Main Drag Slat Conveyor factory rated @ 400 TPH
- New 75 HP motor and all New sprockets and floor liners recently installed
- Aesco Bintop Transfer Slat Conveyor
- NEW 110' Steel Deck above ground truck scale with guard rails

**Controls:**

- ALmix Stationary Split Level Control House
- Allen-Bradley 1600 Amp Motor Control Center
- All NEW ALmix Controls recently were replaced after vandalism.



**AVAILABILITY, PRICE AND CONDITION SUBJECT TO CHANGE BY STANSTEEL®. SPECIFICATIONS ARE ACCURATE TO OUR KNOWLEDGE, HOWEVER, THEY ARE NOT GUARANTEED. ALL PRICES ARE IN U.S. DOLLARS UNLESS OTHERWISE NOTED. EQUIPMENT IS SOLD ON THE BASIS OF AS IS, WHERE IS, THEREFORE, STANSTEEL® RECOMMENDS INSPECTION BY THE BUYER OF ANY USED EQUIPMENT TO DETERMINE SUITABILITY TO THEIR REQUIREMENTS.**

**Genco® and Gencor® are trademarks of Gencor® Industries, Inc. and Stansteel® is not licensed by or related to Gencor® Industries, Inc.**